


IQSHE 31412 G



3/2 avstängningsventil G 1/4"-12mm, slangside avluftande

Betyg: Inte betygsatt ännu

Pris

Pris 233,31 kr

Pris utan moms 186,65 kr

Rabatt

Momsbelopp 46,66 kr

[Ställ en fråga om denna produkt](#)

Beskrivning

Technical data

G G 1/4"

D [mm] 12

Type Tube-side venting

Note RoHS-compliant

Weight 65 g / pc.

Further information

Customs duty number: 84812090

Description

Materials:

Body: nickel-plated brass / PBT, seal: NBR, holding claws: stainless steel, cartridge: nickel-plated ZNDC

Operating pressure:

Max. 10 bar, as well as low vacuum

3/2-ventil* med cyl gänga hane and push-in koppling, Standard: IQSHE 31412 G

Temperature range:

0°C to max. +60°C

Media:

Compressed air, neutral gases

Functional principle:

The 3/2-way valves shut-off the airflow and vent the secondary side.

Application example:

For the control of single-acting small cylinders.

Advantages:

•very compact design

*use these connections only with air. They are not suitable for use with water or other liquids, or other gases than air. The connecting pieces should be tightened onto the stud's hexagon with a spanner

All data are to be understood as non-binding reference values! We do not assume liability for any data selection not confirmed in writing. Unless otherwise specified, pressure values refer to liquids from Group II at +20°C.