

1 TF 8



PTFE slang med rostfritt flätat hölje DN 8

Betyg: Inte betygsatt ännu

Pris

Pris 589,66 kr

Pris utan moms 471,73 kr

Rabatt

Momsbelopp 117,93 kr

[Ställ en fråga om denna produkt](#)

Beskrivning

Technical data

DN [mm] 8

Hose Ø inside [mm] 8.15 - 8.66

Hose Ø external [mm] 10.54 - 11.56

PTFE wall thickness [mm] 0.60

Operating pressure [bar] 207

Burst pressure [bar] 621

Min. bend radius [mm] 102

Further information on 1TF8

Weight 170 g / m

GTIN 4050571186777

Customs duty number 39173100

RoHS compliant Yes

Description - PTFE hose with stainless steel braiding DN 8

PTFE slang med rostfritt flätat hölje: 1 TF 8

Materials:

Wire braiding: 1.4306, Inner tube: PTFE

Temperature range:

-60°C bis +220°C

Operating pressure:

at -60°C to max. +120°C: 100% of the table value, above +120°C: minus 1% of the table value for each additional degree of temperature

Tried and tested for usage in:

Food processing, laboratory and medical equipment, vulcanising presses, steam-iron machines as well as cleaning devices, where a high chemical resistance, thermal stability, elasticity and weather resistance are needed.

All data are to be understood as non-binding reference values! We do not assume liability for any data selection not confirmed in writing. Unless otherwise specified, pressure values refer to liquids from Group II at +20°C.